70NF	OF	ZONES

## FIRE/SMOKE ZONE\* EVALUATION WORKSHEET FOR HEALTH CARE FACILITIES

	2000 LIFE SAFETY CODE				
FACILITY	BUILDING				
ZONE(S) EVALUATED					
PROVIDER/VENDOR NO.	DATE OF SURVEY				
COMPLETE THIS WORKSHEET FOR EACH ZONE. WHERE CONDITIONS ARE THE SAME IN SEVERAL ZONES,					

ONE WORKSHEET CAN BE USED FOR THOSE ZONES.

- **Step 1:** Determine Occupancy Risk Parameter Factors Use Table 1.
  - A. For each Risk Parameter in Table 1, select and circle the appropriate risk factor value. Choose only one for each of the five Risk Parameters.

TABLE 1. OCCUPANCY RISK PARAMETER FACTORS										
Risk Parameters	Risk Parameters Risk Factors Values									
1. Patient	Mobility Status	Mobile	Limited M	obility	No	t Mobile	Not Movable			
Mobility (M)	Risk Factor	1.0	1.0 1.6			3.2	4.5			
2. Patient Density (D)	No. of Patients	1–5	6–10	6–10		11–30	>30			
Delisity (D)	Risk Factor	1.0	1.2	1.2		1.5	2.0			
3. Zone	Floor	<b>1</b> st	2 <sup>rd</sup> or 3 <sup>rd</sup>	4 <sup>th</sup> to	o 6 <sup>th</sup>	7 <sup>th</sup> and Abov	e Basements			
Location (L)	Risk Factor	1.1	1.2	1.4		1.6	1.6			
4. Ratio of Patients to	<u>Patients</u> Attendant	<u>1–2</u> 1	<u>3–5</u> 1	<u>6–10</u> 1		<u>&gt;10</u>	One or More None			
Attendants (T)	Risk Factor	1.0	1.0 1.1		.2	1.5	4.0			
5. Patient Average	Age	Under 65 Yea	ars and Over 1 year		65 Years and Over 1 Year and Younger					
Age (A)	Risk Factor		1.0		1.2					

- **Step 2:** Compute Occupancy Risk Factor (F) Use Table 2.
  - Transfer the circled risk factor values from Table 1 to the corresponding blocks in Table 2.
  - B. Compute F by multiplying the risk factor values as indicated in Table 2.

TABLE 2. OCCUPANCY RISK FACTOR CALCULATION											
OCCUPANCY RISK	M	Х	D	X	L	X	T	Х	A	=	F

- Step 3: Compute Adjusted Building Status (R) Use Table 2.
  - A. If building is classified as "NEW" use Table 3A. If building is classified as "Existing" use Table 3B.
  - B. Transfer the value of F from Table 2 to Table 3A or Table 3B as appropriate. Calculate R.
  - C. Transfer R to the block labeled R in Table 7 on page 4 of the work sheet.

TABLE 3A. (NEW BUILDINGS)	TABLE 3B. (EXISTING BUILDINGS)
1.0 X = =	0.6 x = R

\* FIRE/SMOKE ZONE is a space separated from all other spaces by floors, horizontal exits, or smoke barriers.

SURVEYOR SIGNATURE	TITLE	DATE
FIRE AUTHORITY SIGNATURE	TITLE	DATE

Form CMS-2786T (02/2013) Page 1 **Step 4:** Determine Safety Parameter Values - Use Table 4.

A. Select and circle the safety value for each safety parameter in Table 4 that best describes the conditions in the zone. Choose only one value for each of the 13 parameters. If two or more appear to apply, choose the one with the lowest point value.

			TABL	E 4.						
Safety Parameters			Saf	ety Param	neters Va	lues				
1. Construction	Ту	Combustible pes III, IV, and V		-				NonCombustible Types I and II		
Floor or Zone	000	111	111 200		2HH	000	111	222, 332, 433		
First	-2	0	-2	0	)	0	2	2		
Second	-7	-2	-4	-2	2	-2	2	4		
Third	-9	-7	-9	-7		-7	2	4		
4th and Above	-13	-7	-13	-7	7	-9	-7	4		
Interior Finish     (Corridors and Exits)	Class C -5(0) <sup>f</sup>	Class B 0(3) <sup>f</sup>		Clas						
3. Interior Finish	Class C	Class B		Clas	ss A					
(Rooms)	-3(1) <sup>f</sup>	1(3) <sup>f</sup>		3	3					
4. Corridor	None or Incomplet	e <¹/₂ hour		≥¹/₂ to <	<1 hour		≥1 hour			
Partitions/Walls	-10(0) <sup>a</sup>	0		1(0	)) <sup>a</sup>		2(0) <sup>a</sup>			
5. Doors to Corridor	No Door	<20 min Fl	PR	≥20 mi	n FPR		min FPR and Auto Clos.			
	-10	0		1(0	1(0) <sup>d</sup>		2(0) <sup>d</sup>			
6. Zone Dimensions		Dead End	No I		No Dea	d Ends >30 ft and 2	Zone Length Is			
	>100 ft	>50 ft to 100 ft	30 1	ft to 50 ft	to 50 ft >150		100 ft to 150 ft	<100 ft		
	-6(0) <sup>b</sup>	-4(0) <sup>b</sup>		-2(0) <sup>b</sup> -2(		) <sup>c</sup> 0		1		
7. Vertical Openings	Open 4 or More	Open 2 or	3			losed with	n Indicated Fire Re	sist.		
	Floors	Floors	Floors		<1 hr		hr to <2 hr	≥2 hr		
	-14	-10		C	)		2(0) <sup>e</sup>	3(0) <sup>e</sup>		
8. Hazardous Areas	Double	Deficiency		Single		Deficiency	,	No Deficiencies		
	In Zone		Outside Zone		In Zone		djacent Zone			
	-11	-5		-	-6		-2	0		
9. Smoke Control	No Control		Smoke Barrier Serves Zone				Mech. Ass	isted Syst Zone	ems	
	-5(0) <sup>c</sup>	0								
10. Emergency	<2 Routes				Multip	le Routes				
Movement Routes		Deficien	t		orizontal kit(s)	Horizontal Exit(s)		Direct Exit(s)		
	-8	-2			0		1	5		
11. Manual Fire Alarm	No Man	ual Fire Alarm			Manua	I Fire Alar	m			
				W/O F.	D. Conn.	V	V/F.D. Conn			
		-4			1		2			
12 Smoke Detection							orridor and	Total Spaces		
and Alarm	None	Corridor O	nly		ns Only	Ha	bit. Spaces	In Zone		
	0(3) <sup>g</sup>	2(3) <sup>g</sup>		3(	(3) <sup>g</sup>		4	5		
13. Automatic Sprinklers	None	Corridor a Habit. Spa			ntire Iding					
	0	8			10					

**NOTE:** a Use (0) where parameter 5 is -10.

For SI units: 1 ft = 0.3048 m

Form CMS-2786T (02/2013) Page 2

<sup>&</sup>lt;sup>b</sup> Use (0) where parameter 10 is -8.

c Use (0) on floor with fewer than 31 patients (existing buildings only)

<sup>&</sup>lt;sup>d</sup> Use (0) where parameter 4 is -10.

Use (0) where Parameter 1 is based on first floor zone or on an unprotected type of construction (columns marked "000" or "200")

f Use ( ) if the area of Class B or C interior finish in the corridor and exit or room is protected by automatic sprinklers and Parameter 13 is 0; use ( ) if the room with existing Class C interior finish is protected by automatic sprinklers, Parameter 4 is greater than or equal to 1, and Parameter 13 is 0.

<sup>&</sup>lt;sup>9</sup> Use this value in addition to Parameter 13 if the entire zone is protected with quick-response automatic sprinklers.

- Step 5: Compute Individual Safety Evaluations Use Table 5.
  - A. Transfer each of the 13 circled Safety Parameter Values from Table 4 to every unshaded block in the line with the corresponding Safety Parameter in Table 5. For Safety Parameter 13 (Sprinklers) the value entered in the People Movement Safety column is recorded in Table 5 as ½ the corresponding value circled in Table 4.
  - B. Add the four columns, keeping in mind that any negative numbers deduct.
  - C. Transfer the resulting total values for S<sub>1</sub>, S<sub>2</sub>, S<sub>3</sub>, S<sub>6</sub> to blocks labeled S<sub>1</sub>, S<sub>2</sub>, S<sub>3</sub>, S<sub>6</sub> in Table 7 on page 4 of this sheet.

TABLE 5. INDIVIDUAL SAFETY EVALUATIONS								
Safety Parameters	Containment Safety (S <sub>1</sub> )	Extinguishment Safety (S <sub>2</sub> )	People Movement Safety (S <sub>3</sub> )	General Safety (S <sub>4</sub> )				
1. Construction								
Interior Finish     (Corr. and Exit)								
3. Interior Finish (Rooms)								
4. Corridor Partitions/Walls								
5. Doors to Corridor								
6. Zone Dimensions								
7. Vertical Openings								
8. Hazardous Areas								
9. Smoke Control								
10. Emergency Movement Routes								
11. Manual Fire Alarm								
12. Smoke Detection and Alarm								
13. Automatic Sprinklers			÷ 2 =					
Total Value	S1=	S <sub>2</sub> =	S3=	S4=				

## TABLE 6. MANDATORY SAFETY REQUIREMENTS (FOR USE IN HOSPITALS OR NURSING HOMES) **People Movement** Containment **Extinguishment** (Sa) (S<sub>b</sub>) (Sc) **Zone Location** New Exist. New Exist. New Exist. 1<sup>st</sup> story 11 5 15(12)<sup>a</sup> 4 $8(5)^{a}$ 1 2<sup>nd</sup> or 3rd story<sup>b</sup> 9 17(14)<sup>a</sup> 6 $10(7)^{a}$ 15 3 4th story or higher 18 9 19(16)<sup>a</sup> 11(8)<sup>a</sup> 3

- a. Use ( ) in zones that do not contain patient sleeping rooms.
- b. For a 2<sup>nd</sup> story zone location in a sprinklered EXISTING facility, as an alternative to the mandatory safety requirement values set specified in the table, the following mandatory values *set* shall be permitted to be used: S<sub>a</sub>=7, S<sub>b</sub>=10, and S<sub>c</sub>=7

Form CMS-2786T (02/2013 ) Page 3

- **Step 6:** Determine Mandatory Safety Requirement Values Use Table 6.
  - A. Using the classification of the building (i.e., New or Existing) and the floor where the zone is located circle the appropriate value in each of the three columns in Table 6.
  - B. Transfer the three circled values from Table 6 to the blocks marked  $S_a$ ,  $S_b$ , and  $S_c$  in Table 7.
  - C. For each row check "Yes" if the value in the answer block is zero or greater. Check "No" if the value in the answer block is a negative number.

	TABLE 7. ZONE FIRE SAFETY EQUIVALENCY EVALUATION							
Containment Safety (S <sub>1</sub> )	minus	Mandatory Containment (S₃)	≥ 0	S <sub>1</sub> S <sub>a</sub> C = C				
Extinguishment Safety (S <sub>2</sub> )	minus	Mandatory Extinguishment (S <sub>b</sub> )	≥ 0	S <sub>2</sub> S <sub>b</sub> E				
People Movement Safety (S <sub>3</sub> )	minus	Mandatory People Movement (S <sub>c</sub> )	≥ 0	S <sub>3</sub> - S <sub>c</sub> P				
General Safety (S <sub>4</sub> )	minus	Occupancy Risk (R)	≥ 0	S <sub>4</sub> R G =				

	TABLE 8. FACILITY FIRE SAFETY REQUIREMENTS WORKSHEET	Γ		
1	mplete one copy of this worksheet for each facility. r each consideration, select and mark the appropriate column.	Met	Not Met	Not Applic.
A.	Building utilities conform to the requirements of Section 9.1.			
B.	In new facilities only, life-support systems, alarms, emergency communication systems, and illumination of generator set locations are powered as prescribed by 18.5.1.2 and 18.5.1.3.			
C.	Heating and air conditioning systems conform with the air conditioning, heating, and ventilating systems requirements within Section 9.2, except for enclosure of vertical openings, which have been considered in Safety Parameter 7 of Worksheet 4.7.6.			
D.	Fuel-burning space heaters and portable electrical space heaters are not used.			
E.	There are no flue-fed incinerators.			
F.	An evacuation plan is provided and fire drills conducted in accordance with 18.7.1/18.7.2 and 19.7.1/19.7.2.			
G.	Smoking regulations have been adopted and implemented in accordance with 18.7.4 and 19.7.4.			
H.	Draperies, upholstered furniture, mattresses, furnishings, and decoration combustibility is limited in accordance with 18.7.5 and 19.7.5.			
I.	Fire extinguishers are provided in accordance with the requirements of 18.3.5.4 and 19.3.5.6.			
J.	Exit signs are provided in accordance with the requirements of 18.2.10.1 and 19.2.10.			
K.	Emergency lighting is provided in accordance with 18.2.9.1 or 19.2.9.			
L.	Standpipes are provided in all new high rise buildings as required by 18.4.2.			

CONCLUSIONS
1. All of the checks in Table 7 are in the "Yes" column. The level of fire safety is at least equivalent to that prescribed by the <i>Life Safety Code</i> .*
2.  One of more of the checks in Table 7 are in the "No" column. The level of fire safety is not shown by this system to be equivalent to that prescribed by the Life Safety Code.*
*The equivalency covered by this worksheet includes the majority of considerations covered by the <i>Life Safety Code</i> . There are a few considerations that are not evaluated by this method. These must be considered separately. These additional considerations are covered in Table 8, the "Facility Fire Safety Requirements Worksheet." One copy of this separate worksheet is to be completed for each facility.

According to the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number. The valid OMB control number for this information collection is 0938-0242. The time required to complete this information collection is estimated to average 5 minutes per response, including the time to review instructions, search existing data resources, gather the data needed, and complete and review the information collection. If you have any comments concerning the accuracy of the time estimate(s) or suggestions for improving this form, please write to: CMS, Attn: PRA Reports Clearance Officer, 7500 Security Boulevard, Baltimore, Maryland 21244-1850.

Form CMS-2786T (02/2013) Page 4

## FIRE SAFETY SURVEY REPORT CRUCIAL DATA EXTRACT (TO BE USED WITH CMS-2786 FORMS)

PROVIDER NUMBER	FACILITY NAME				SURVEY DATE
K1					* K4
K6 DATE OF PLAN APPROVAL	K3 MULTIPLE CONSTRUTOTAL NUMBER OF THIS BUILD	ILDINGS			A BUILDING B WING C FLOOR D APARTMENT UNIT
LSC FORM INDICATOR	,				/ED UNDER CHAPTER 21
	000 EXISTING		ALL	(16 BEDS OR LES 1 PROMPT 2 SLOW	SS)
13 2786R 2	000 NEW	K8:		3 IMPRACTICAL	
15 2786U 20 ICF/MR 16 2786V, W, X 20 17 2786V, W, X 20	000 EXISTING 000 NEW  R Form 000 EXISTING 000 NEW  DF FORM USED FROM ABO  wrked as not applicable	AP K8:	ARTMENT	4 PROMPT 5 SLOW 6 IMPRACTICAL HOUSE 7 PROMPT 8 SLOW 9 IMPRACTICAL CORE HERE e.g. 2.5	
*K9: FACILITY MEETS LSC E  A1. (COMP. WITH ALL PROVISIONS)	A2. (ACCEPTABLE POC)	A3. (WAI	VERS)	A4. [ [ FSES)	A5. PERFORMANCE BASED DESIGN)
B.	FL	A JLLY SPR	INKLERED are sprinklered)	B. PARTIALLY SPRIN (Not all required areas are	

Form CMS-2786T (02/2013) Page 5

<sup>\*</sup> MANDATORY